Engineered by






# powerLine

CREEP-FEED GRINDING MACHINE





WORK PIECES UP TO 3000×700×650MM [L×W×H]









## **CREEP-FEED GRINDING 2.0**

- Extreme high rigidity
- Spindle power up to 105 kW



Grinding spindle with pre-loaded precision bearings



High table load capacity

## ROBUST AND ECONOMICAL





### powerLine - CREEP-FEED GRINDING 2.0

- Large grinding widths and lengths up to 3 meters as compact single column construction
- Highest rigidity and grinding performance for high productivity and material removal rate
- Welded and tempered steel construction
- Linear guideways in all axes
- Full machine enclosure
- Traveling table machine
- All axes with ball screws
- Siemens SINUMERIK ONE control
  Z-axis via traveling headstock for
- more stiffness
- Various dressing and measuring device options




Table-mounted profile roll dressing unit

TECHNICAL DATA

Continuous dressing device for grinding wheels up to 300 mm



Grinding of hedge trimmers

TECHNICAL DATA				
powerLine	10	15	20	30
Table drive	Ball screw	Ball screw	Ball screw	Ball screw
Grinding width [mm]	700	700	700	700
Grinding length [mm]	1000	1500	2000	3000
Distance spindle center to table [mm]	900/1100			
Spindle power [kW]	52/70/90/105			
Grinding wheel [mm]		400 × 60 × 127 500 × 150 × 203		

## **GET IN TOUCH WITH US TODAY** TOGETHER WE WILL FIND A SOLUTION FOR YOUR REQUIREMENTS

### 12-2022 WE RESERVE THE RIGHT FOR TECHNICAL CHANGES!

### ELB-SCHLIFF Werkzeugmaschinen GmbH

Phone: +49 6028 408 0 info@elb-schliff.de www.elb-schliff.de